

1019 LUBRICATION SYSTEM UNIVERSAL TO ALL SERIES ROTATING CONTROL DEVICES

The Washington Rotating Lubricator Model 1019 is a pressurized system designed to give long trouble-free service to all of our rotating assemblies. This system provides a continuous source of fresh oil to the rotating assembly, completely submerging the bearing and seals in a bath of pressurized oil. By metering the oil through the internal seals, all foreign matter is excluded from the internal rotating parts, enabling long trouble-free service from your Rotating Control Device.



WHEN ORDERING, PLEASE SPECIFY:

1. model number
2. lower flange size
3. outlet flange size
4. Kelly size and shape
5. drill pipe size
6. drilling environment
7. high temperature, if applicable.

All air bowls can be fitted with female collared or flanged outlets at your request. All air bowls can be double drilled at your request.

REV 11/14

Arch Rental, LLC

P: (724) 228-1220 | F: (724) 228-8912
63 Springfield Avenue | P.O. Box 261
Washington, PA 15301
www.archrental.com

Our test pressures have been established through controlled test procedures. As a result of the ever-changing environment of well drilling operations along with wear and tear on equipment, which erodes longevity and safe operating parameters, Washington Rotating Control Heads, Inc., its Business Units, Agents and Affiliates make no warranty either expressed or implied on the test pressures contained herein. Washington Rotating Control Heads, Inc. does not under any circumstances recommend that its rotating control devices be used as primary blow out prevention equipment.